

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method of forwarding requests for content from a client over a network, comprising:
 - (a) receiving a request for content and based on a determination of the request, determining at least one type of the requested content;
 - (b) when the type of the requested content is determined to be dynamic, forwarding the request to a content server that enables access to the dynamic content; and
 - (c) when the type of the requested content is determined to be static, forwarding the request to a plurality of caches that enable access to the static content, wherein the plurality of caches include at least one hot cache.
2. (Original) The method of claim 1, wherein the hot cache caches static content when a frequency of requests for the static content exceeds a threshold.
3. (Original) The method of claim 1, further comprising when the static content is unavailable in the hot cache, forwarding the request to another cache in the plurality of caches.
4. (Original) The method of claim 1, further comprising when the static content is unavailable from any one of the plurality of caches, forwarding the request to the content server that enables access to the static content.
5. (Previously Presented) The method of claim 1, further comprising examining the request for an extension indicating that a process is performed in response to the request, wherein the process includes an application program or a script.
6. (Original) The method of claim 1, wherein the content includes information associated with a plurality of resource identifiers.
7. (Original) The method of claim 6, wherein the resource identifiers are uniform resource locators (URLs).

(c) the cache is coupled to the forwarder, wherein the cache sends content to the client in response to each request that is forwarded to the cache.

13. (Previously Presented) The system of claim 26, wherein the cache includes an additional cache, and wherein the hot cache, the regular cache, and the additional cache are arranged in a hierarchical order for receiving each forwarded request for content from the forwarder, and wherein each cache that receives the forwarded request for content that is unavailable, generates an additional request for the content and sends the additional request to the forwarder.
14. (Original) The system of claim 12, wherein the forwarder is coupled to the content server over a wide area network/local area network.
15. (Original) The system of claim 12, wherein the forwarder is coupled to the content server over a communications medium.
16. (Previously Presented) The system of claim 26, wherein the request is associated with information, and wherein the information includes a location at which the request is generated, the frequency of requests for the content, or the nature of the content requested.
17. (Original) The system of claim 16, wherein the forwarder is further structured to forward requests to the content server when the information indicates that the request is generated by the regular cache.
18. (Original) The system of claim 16, wherein the forwarder is further structured to forward requests to the hot cache when the information indicates that the rate of requests exceeds a threshold.
19. (Original) The system of claim 16, wherein the forwarder is further structured to forward requests to the regular cache when the information indicates that the request is generated by the hot cache.
20. (Previously Presented) The system of claim 26, wherein the hot cache and the regular cache are located on one device.
21. (Original) The system of claim 12, wherein the server uses a hash table to calculate the number of requests for the content.

23. (Original) The system of claim 22, wherein the resource identifiers are uniform resource locators (URLs).

(a) means for receiving a request for content and determining at least one type of the requested content based on the request;

(c) when the type of the requested content is determined to be static, means for forwarding the request to a plurality of caches that enable access to the static content, wherein the plurality of caches include at least one hot cache.

(a) a forwarder that receives each request for content and forwards each request to at least one of a content server and a cache based on a determination of a type of content requested by the request;

(c) another transceiver that couples the cache to the forwarder, wherein the cache sends content to the client in response to each request that is forwarded to the cache based on a determination of the request.

{S:\08204\000s097-us0\80040723.DOC [REDACTED] }

27. (New) A method of forwarding requests for content from a client over a network, comprising:

- receiving a request for content and determining if the request is for a dynamic type of content;
- selectively communicating with at least one of a plurality of caches based on an affirmative determination of the request; and
- providing a response to the request for content based on the determination of the request.

28. (New) The method of Claim 27, further comprising selectively communicating with at least one content server based on the determination of the request.